

BOT-2CS/1200/xxx



1

3



"SKA-100"

| | | | |
|-----|---|---|----------|
| max | : | 1200 | (.) |
| min | : | 1 | () |
| | : | 1265 | |
| | : | 265 | |
| | : | 2900 | |
| | : | 1200 | |
| | : | 2200 | |
| | : | 2x Ø460/350, | 1000 |
| | : | 350 | |
| | : | 3000 | |
| | : | RF, RJ | |
| | : | 1 - | () |
| | : | | 5..100%, |
| | : | API, DIN 3230 part.3 - ANSI/FCI 70-2, BS 6755 | |
| | : | 6.5 | 1100 / |
| | : | 3 + T, 380 ,50 , 12 | |
| | : | 3900(L) x 3700(P) x 4920(H) | |

OP001M

OP002M

AC001

AC002

(*)

| DN | 1000 | 1200 | 1300 | 1400 | 1500 | 1600 | 1700 | 1800 | 1900 | 2000 | 2200 | 2400 |
|-------|------|------|------|------|------|------|------|------|------|------|------|------|
| PN-10 | | | | | | | | | | | | |
| PN-16 | | | | | | | | | | | | |
| PN-25 | | | | | | | | | | | | |
| PN-40 | | | | | | | | | | | | |
| PN-64 | | | | | | | | | | | | |